

# MSE 1

**SURROUND EXPANDER / DOLBY DIGITAL AC-3, DTS**

# McIntosh

**The Compendium**



**FRONT PANEL:** Glass with illuminated teal/gold nomenclature. Channel status: LS, BS, RS, SUB. Indicator for EXPAND mode. Digital readout for DELAY/TRIM. ⚡ Touch buttons: MODE: AUTO, MANUAL. SYS CAL, DELAY, POWER: OFF or ON (with indicator), ▼ LEVEL, LEVEL ▲, TRIM (with indicator), STANDBY/ON.



**BACK PANEL:** Power cord receptacle. OUTPUTS: Left / Right BACK 2, BACK 1 / SUBWOOFER, Left / Right SURR. Left / Right ANALOG INPUT. DATA: IN and OUT. POWER CONTROL: IN and OUT. SYSTEM CALIBRATE switch: AUTO or MAN. SPEAKER SETTINGS: BACK 2 and 1: NONE, SMALL or LARGE. SURROUND: SMALL, LARGE. SUBWOOFER: OFF or ON.

**SPECIFICATIONS:** Frequency response: Surround small speakers: 80Hz-20,000Hz, subwoofer 20Hz to 80Hz. Surround large speakers: 20Hz-20,000. Rated output: 2.0V for full bit (6.0V max). Output impedance: less than 100 ohms. Total harmonic distortion: 0.005% at all outputs. Sensitivity: 200 mV. Signal to noise ratio all outputs: >98dB A weighted. Voltage gain: unity from input to output, ±6dB with trim level.



**MSE 1** - Sold from ???? - . S/N: SG1001~?????

Size 3-9/16"H, 17-1/2"W and 5-11/16"D. Weight 19-1/2 lb. **\$2,500.00**