

# MC 150

## STEREO POWER AMPLIFIER

McIntosh  
The Compendium



**FRONT PANEL:** Glass with illuminated teal/gold nomenclature. Illuminated POWER OUTPUT meters (linear WATTS or DECIBELS). LEFT and RIGHT POWER GUARD lights. ⚡ METER switch: WATTS or HOLD. POWER switch: OFF/REMOTE or ON.



**BACK PANEL:** POWER CONTROL jacks: IN and OUT. FUSE. Power cord receptacle. RIGHT and LEFT gold plated speaker OUTPUT terminals. MODE switch: STEREO, MONO BRIDGED or MONO PARALLEL. LEFT and RIGHT LEVEL controls: 1.4V to 2.5V. UNBALANCED RIGHT/MONO and LEFT audio INPUTS. BALANCED RIGHT/MONO and LEFT audio INPUTS.

**SPECIFICATIONS:** 150w/ch. Response 20-20kHz (+0 -0.25dB). Distortion 0.005%. Noise and hum - 110dBA. Output impedance 2, 4 and 8 ohms. Damping factor 40 or greater. Input impedance 20k. Input sensitivity 1.4v. Sentry Monitor. Power Guard.

# MC 150

STEREO POWER AMPLIFIER

McIntosh  
The Compendium

---



**MC 150** - Sold from 1995 - 1997. S/N: AM1001~?????

Size 5-3/8"H, 17-1/2"W and 16-1/2"D. Weight 59 lb. **\$3,000.00**