

MC 2002

STEREO POWER AMPLIFIER

McIntosh
The Compendium



FRONT PANEL: Glass with illuminated teal/gold nomenclature and anodized black aluminum panel. Illuminated left and right **POWER OUTPUT** meters (linear **WATTS** or **dB**). **POWER GUARD** lamps: **LEFT**, **TEMP** and **RIGHT**. ⚡ Illuminated **POWER** switch: **ON** or **OFF**. **PANLOC** buttons.



BACK PANEL: LEFT and RIGHT speaker **OUTPUT** barrier strip. **MODE** switch: **STEREO** or **MONO**. **INPUT LEVEL** switch: **2.5V** or **1.4V**. ⚡ **UNSWITCHED AC** outlet. Power cord. **FUSE**. LEFT and **RIGHT / MONO** audio **INPUT**. Panloc mounting.

SPECIFICATIONS: **200w/ch** into 8 ohms, **300w/ch** into 4 ohms. (**600w** mono into 8 ohms). Response 20-20kHz (+0 -0.25dB). Distortion 0.01%. Noise and hum -100dB. Output direct coupled for 4 to 8 ohms. Damping factor 100 or greater. Input impedance 20k. Input sensitivity 1.4v or 2.5v. *Sentry Monitor. Power Guard.*



MC 2002

STEREO POWER AMPLIFIER

McIntosh
The Compendium



MC 2002 - Sold from 1984 - November 1988. S/N: DG1001~DG2843 (1,842 UNITS)
Size 7-1/8"H, 16-3/16"W and 14-1/2"D. Weight 50 lb. **\$1,850.00**