

MC 2150

STEREO POWER AMPLIFIER

McIntosh
The Compendium



FRONT PANEL: Gold anodized aluminum/black. LEFT and RIGHT POWER GUARD lamps: LIMIT or NORMAL. SYSTEM TEST digital readout. ⚡ LEFT GAIN control. SPEAKERS switch: OFF or ON. RIGHT/MONO GAIN control. HEADPHONES jack. POWER switch: OFF or ON.



BACK PANEL: LEFT and RIGHT speaker OUTPUT barrier strips. Power cord. AC OUTLET. FUSE. MODE switch: STEREO, MONO BRIDGE or MONO PARALLEL. LEFT and RIGHT (MONO) audio INPUT. INPUT LEVEL switch: 2.5V or .75V.

SPECIFICATIONS: 150w/ch. (300w mono). Response 20-20kHz (+0 -0.25dB). Distortion 0.02%. Noise and hum -95dB. Output impedance 1, 2, 4, and 8 ohms. (0.5, 1, 2, 4, 8 and 16 ohms in mono). Damping factor 30 or greater Input impedance 50k. Input sensitivity 0.75v or 2.5v. Headphone impedance: low. *Sentry Monitor. Power Guard.*

MC 2150

STEREO POWER AMPLIFIER

McIntosh
The Compendium



MC 2150 - Sold from September 1982 - 1986. S/N: DA1001~DA1391 (390 UNITS)
Size 5-7/32"H, 16"W and 14-1/2"D. Weight 58 lb. **\$1,925.00**