

MC 2155

STEREO POWER AMPLIFIER

McIntosh
The Compendium



FRONT PANEL: Glass with illuminated teal/gold nomenclature. Illuminated left and right power level meters (linear WATTS or DECIBELS). SYSTEM TEST digital readout. POWER GUARD lamps: NORMAL or LIMIT. ⚡ LEFT GAIN control. METER RANGE SWITCH: -20, -10, 0, WATTS and HOLD. SPEAKERS switch: OFF or ON. RIGHT/MONO GAIN control. HEADPHONES jack. POWER switch: OFF or ON. PANLOC buttons.



BACK PANEL: LEFT and RIGHT speaker OUTPUT barrier strips. Power cord. AC OUTLET. FUSE. MODE switch: STEREO, MONO BRIDGE or MONO PARALLEL. LEFT and RIGHT (MONO) audio INPUT. INPUT LEVEL switch: 2.5V or .75V. Panloc mounting.

SPECIFICATIONS: 150w/ch. (300w mono). Response 20-20kHz (+0 -0.25dB). Distortion 0.02%. Noise and hum -95dB. Output impedance 1, 2, 4 and 8. (0.5, 1, 2, 4, 8 and 16 ohms in mono). Damping factor 30 or greater Input impedance 50k. Input sensitivity 0.75v or 2.5v. Headphone impedance: low. Sentry Monitor. Power Guard.



MC 2155

STEREO POWER AMPLIFIER

McIntosh
The Compendium



MC 2155 - Sold from October 1981 - 1986. S/N: CW1001~CW2696 (1,695 UNITS)
Size 5-7/16"H, 16"W and 14-1/2"D. Weight 65 lb. **\$2,295.00**