

MC 2200

STEREO POWER AMPLIFIER

McIntosh
The Compendium



FRONT PANEL: Gold anodized aluminum and black panel. LEFT and RIGHT output mode lamps: LIMIT or NORMAL. ⚡ LEFT GAIN control. RIGHT/MONO GAIN control. HEADPHONES jack. POWER switch: OFF or ON.



BACK PANEL: LEFT and RIGHT speaker OUTPUT barrier strips. Power cord. AC OUTLET. FUSE. POWER GUARD switch: NORMAL or OUT. MODE switch: STEREO or MONO. Left and Right (MONO) audio INPUT. INPUT LEVEL switch: 2.5v or .75v.

SPECIFICATIONS: 200w/ch. (400w mono). Response 20-20kHz (+0 -0.25dB). Distortion 0.1%. Noise and hum -95dB. Output impedance 1, 2, 4, and 8 ohms. (0.5, 1, 2, and 4 ohms in mono). Damping factor 16 or greater. Input impedance 100k. Input sensitivity 0.75v or 2.5v. Headphone impedance: low. Sentry Monitor. Power Guard.



MC 2200

STEREO POWER AMPLIFIER

McIntosh

The Compendium



MC 2200 - Sold from May 1976 - February 1982. S/N: AU1001~AU4600 (3,599 UNITS)
Size 6-31/32"H, 16"W and 14-1/2"D. Weight 73 lb. **\$1,199.00**