

# MC 2205

## STEREO POWER AMPLIFIER

McIntosh  
The Compendium



**FRONT PANEL:** Glass with illuminated teal/gold nomenclature. Illuminated left and right power level meters (linear WATTS or DECIBELS). METER function lamps: WATTS, HOLD or DECIBELS. OUTPUT MODE lamps: NORMAL or LIMIT. ⚡ LEFT GAIN control. METER RANGE SWITCH: -20, -10, 0, WATTS and HOLD. HEADPHONES jack. SPEAKERS switch: OFF or ON. RIGHT/MONO GAIN control. POWER switch: OFF or ON. PANLOC buttons.



**BACK PANEL:** LEFT and RIGHT speaker OUTPUT barrier strips. Power cord. AC OUTLET. FUSE. POWER GUARD switch: NORMAL or OUT. MODE switch: STEREO or MONO. Left and Right(MONO) audio INPUT. INPUT LEVEL switch: 2.5v or .75v. Panloc mounting.

**SPECIFICATIONS:** 200w/ch. (400w mono). Response 20-20kHz (+0 -0.25dB). Distortion 0.1%. Noise and hum -95dB. Output impedance 1, 2, 4 and 8 ohms. (0.5, 1, 2, and 4 ohms in mono). Damping factor 16 or greater. Input impedance 100k. Input sensitivity 0.75v or 2.5v. Headphone impedance: low. Sentry Monitor. Power Guard.



# MC 2205

## STEREO POWER AMPLIFIER

McIntosh  
The Compendium



**MC 2205** - Sold from December 1975 - 1979. S/N: AX1001~AX9999 & CH1001~CH4299 (12,296 UNITS)

Size 7-1/8"H, 16-3/16"W and 14-1/2"D. Weight 85 lb. **\$1,649.00**