

# MC 2250

## STEREO POWER AMPLIFIER

McIntosh  
The Compendium



**FRONT PANEL:** Gold anodized aluminum and black panel. LEFT and RIGHT POWER GUARD lamps: LIMIT or NORMAL. SYSTEM TEST digital readout. ⚡ LEFT GAIN control. SPEAKERS switch: OFF or ON. RIGHT/MONO GAIN control. HEADPHONES jack. POWER switch: OFF or ON.



**BACK PANEL:** LEFT and RIGHT speaker OUTPUT barrier strips. Power cord. AC OUTLET. FUSE. MODE switch: STEREO, MONO BRIDGE or MONO PARALLEL. LEFT and RIGHT (MONO) audio INPUT. INPUT LEVEL switch: 2.5V or .75V.

**SPECIFICATIONS:** 250w/ch. (500w mono). Response 20-20kHz (+0 -0.25dB). Distortion 0.02%. Noise and hum -95dB. Output impedance 1, 2, 4, and 8 ohms. (0.5, 1, 2, 4, 8 and 16 ohms in mono). Damping factor 30 or greater. Input impedance 50k. Input sensitivity 0.75v or 2.5v. Headphone impedance: low. Sentry Monitor. Power Guard.

# MC 2250

## STEREO POWER AMPLIFIER

McIntosh  
The Compendium



**MC 2250** - Sold from February 1982 - 1987. S/N: DB1001~DB1500 (499 UNITS)  
Size 6-31/32"H, 16"W and 14-1/2"D. Weight 80 lb. **\$2,495.00**