

# MC 2255

STEREO POWER AMPLIFIER

# McIntosh

The Compendium



**FRONT PANEL:** Glass with illuminated teal/gold nomenclature. Illuminated left and right power level meters (linear WATTS or DECIBELS). METER function lamps: WATTS, HOLD or DECIBELS. SYSTEM TEST digital readout. POWER GUARD lamps: NORMAL or LIMIT. ⚡ LEFT GAIN control. METER RANGE SWITCH: -20, -10, 0, WATTS and HOLD. HEADPHONES jack. SPEAKERS switch: OFF or ON. RIGHT/MONO GAIN control. POWER switch: OFF or ON. PANLOC buttons.



**BACK PANEL:** LEFT and RIGHT speaker OUTPUT barrier strips. Power cord. AC OUTLET. FUSE. MODE switch: STEREO, MONO BRIDGE or MONO PARALLEL. LEFT and RIGHT (MONO) audio INPUT. INPUT LEVEL switch: 2.5V or .75V. Panloc mounting.

**SPECIFICATIONS:** 250w/ch. (500w mono). Response 20-20kHz (+0 -0.25dB). Distortion 0.02%. Noise and hum -95dB. Output impedance 1, 2, 4 and 8. (0.5, 1, 2, 4, 8 and 16 ohms in mono). Damping factor 30 or greater. Input impedance 50k. Input sensitivity 0.75v or 2.5v. Headphone impedance: low. Sentry Monitor. Power Guard.

# MC 2255

## STEREO POWER AMPLIFIER

# McIntosh

The Compendium



**MC 2255** - Sold from April 1981 - June 1986. S/N: CT1001~CT5700 (4,699 UNITS)  
Size 7-1/8"H, 16-3/16"W and 14-1/2"D. Weight 82 lb. **\$2,995.00**