

# MC 275 CE

## STEREO POWER AMPLIFIER

McIntosh  
The Compendium



**CONTROLS & CONNECTORS:** Chrome/black chassis. LEFT and RIGHT speaker OUTPUT barrier strips for 4, 8 and 16 OHMS. Left and Right (MONO) audio XLR BALANCED INPUTS jacks. Left and Right (MONO) UNBALANCED GAIN controls: 2.5V to 1.0V. ⚡ Power cord. AC outlet. FUSE. MODE switch: MONO or STEREO. INPUT switch: BALANCED or UNBALANCED. Left and Right (MONO) audio UNBALANCED INPUTS.



McIntosh 275



# MC 275 CE

## STEREO POWER AMPLIFIER

# McIntosh

## The Compendium

**SPECIFICATIONS:** 75w/ch stereo, 150w mono. Response 20-20kHz (+0 -0.2dB). Distortion 0.5%. Noise & hum -100dB (A weighted). Output impedance 4, 8, 16 ohms. (2, 4, and 8 ohms in mono). 25V line. Damping factor greater than 10. Input impedance: 100k unbalanced, 180k balanced. Input sensitivity: 1.0V unbalanced, 2.0V balanced.

**TUBES:** 4-KT88/6550 output, 3-12AX7A, 4-12AZ7. Solid state rectifier bridge.



**MC 275 CE** - Sold from 1993 - 1996. S/N: E????~E???? (3,500 UNITS)

Size 7-1/2"H, 12"W and 16"D. Weight 67 lb. **\$4,000.00**