

# MC 275 MK III

STEREO POWER AMPLIFIER

McIntosh

The Compendium

---



**CONTROLS & CONNECTORS:** Stainless steel/black chassis. LEFT and RIGHT speaker OUTPUT barrier strips for 4, 8 and 16 OHMS. Left and Right (MONO) audio XLR BALANCED INPUTS jacks. Left and Right (MONO) UNBALANCED LEVEL controls: 2.5V to 1.0V. ⚡ POWER switch OFF or ON. Left and Right (MONO) audio UNBALANCED INPUTS. MODE switch: MONO or STEREO. INPUTS switch: BALANCED or UNBALANCED.

**RIGHT SIDE CONNECTORS:** Power cord receptacle. FUSE.



# MC 275 MK III

## STEREO POWER AMPLIFIER

# McIntosh

## The Compendium

**SPECIFICATIONS:** 75w/ch stereo, 150w mono. Response 20-20kHz (+0 -0.2dB). Distortion 0.5%. Noise & hum -100dB (A weighted). Output impedance 4, 8, 16 ohms. (2, 4, and 8 ohms in mono). 25V line. Damping factor greater than 10. Input impedance: 100k unbalanced, 180k balanced. Input sensitivity: 1.0V unbalanced, 2.0V balanced.

**TUBES:** 4-KT88/6550 output, 3-12AX7A, 4-12AZ7. Solid state rectifier bridge.



**MC 275 MK III** - Sold from 19?? - 19??. S/N: ?????~????? (??0 UNITS)

Size 7-1/2"H, 12"W and 16"D. Weight 67 lb. **\$4,000.00**