

MC 275 MK IV (EARLY) STEREO POWER AMPLIFIER

McIntosh
The Compendium



CONTROLS & CONNECTORS: Polished stainless steel/black chassis. LEFT and RIGHT speaker OUTPUT barrier strips for 4, 8 and 16 OHMS. Left and Right (MONO) audio XLR BALANCED INPUTS jacks. Left and Right (MONO) UNBALANCED LEVEL controls: 2.5V to 1.0V. ⚡ POWER switch OFF or ON. Left and Right (MONO) audio UNBALANCED INPUTS. MODE switch: MONO or STEREO. INPUTS switch: BALANCED or UNBALANCED.



SPECIFICATIONS: 75w/ch stereo into 4, 8 or 16 ohms, 150w mono into 2, 4, or 8 ohms. Response 20-20kHz (+0 -0.2dB). Distortion 0.5%. Noise & hum -100dB (A weighted). Output impedance 4, 8, 16 ohms. (2, 4, and 8 ohms in mono). 25V line. Damping factor greater than 14. Input impedance: 100k unbalanced, 180k balanced. Input sensitivity: 1.2V unbalanced, 2.5V balanced.

TUBES: 4-KT88/6550 output, 3-12AX7A, 4-12AT7. Solid state rectifier bridge.



MC 275 MK IV (EARLY) STEREO POWER AMPLIFIER

McIntosh
The Compendium



MC 275 MKIV (EARLY) "Spotting features": **1.** Speaker connectors are barrier strips. **2.** Unbalanced inputs and mode and inputs switches are located on flat front. **3.** XLR inputs are white and with a gold surround. **4.** Gain controls.

MC 275 MKIV (EARLY) - Sold from March 2004-December 2006. S/N: VN1001~?????
Size 8-1/4"H, 12"W and 16-1/2"D. Weight 67 lb. **\$3,500.00**