

MC 275 MK IV (LATE)

STEREO POWER AMPLIFIER

McIntosh
The Compendium



CONTROLS & CONNECTORS: Polished stainless steel/black chassis. LEFT speaker OUTPUT binding posts: COM, 4 Ω , 8 Ω , 16 Ω . RIGHT speaker OUTPUT binding posts: COM, 4 Ω , 8 Ω , 16 Ω . MODE switch: MONO or STEREO. Left and Right audio XLR BALANCED INPUTS jacks. INPUTS switch: BALANCED or UNBALANCED. Left and Right (MONO) audio UNBALANCED INPUTS. ⚡ POWER switch OFF or ON.



SPECIFICATIONS: 75w/ch stereo into 4, 8 or 16 ohms, 150w mono into 2, 4, or 8 ohms. Response 20-20kHz (+0 -0.2dB). Distortion 0.5%. Noise & hum -100dB (A weighted). Output impedance 4, 8, 16 ohms. (2, 4, and 8 ohms in mono). 25V line. Damping factor greater than 14. Input impedance: 100k unbalanced, 180k balanced. Input sensitivity: 1.2V unbalanced, 2.5V balanced.

TUBES: 4-KT88/6550 output, 3-12AX7A, 4-12AT7. Solid state rectifier bridge.

MC 275 MK IV (LATE)

STEREO POWER AMPLIFIER

McIntosh
The Compendium

MC 275 MKIV (LATE) "Spotting features": **1.** Speaker connectors are binding posts. **2.** Unbalanced inputs and mode and inputs switches are located on angled front. **3.** XLR inputs are black with no surround. **4.** No gain controls.

MC 275 MKIV (LATE) - Sold from January 2007-?????. S/N: WM1001~?????

Size 8-1/4"H, 12"W and 16-1/2"D. Weight 67 lb. **\$3,500.00**