

# MC 300

## STEREO POWER AMPLIFIER

McIntosh  
The Compendium



**FRONT PANEL:** Glass with illuminated teal/gold nomenclature. Illuminated POWER OUTPUT meters (linear WATTS or DECIBELS). LEFT and RIGHT POWER GUARD lights. ⚡ METER switch: WATTS or HOLD. POWER switch: OFF/REMOTE or ON.



**BACK PANEL:** POWER CONTROL jacks: IN and OUT. FUSE. Power cord receptacle. RIGHT and LEFT gold plated speaker OUTPUT terminals. MODE switch: STEREO, MONO BRIDGED or MONO PARALLEL. LEFT and RIGHT LEVEL controls: 1.4V to 2.5V. UNBALANCED RIGHT/MONO and LEFT audio INPUTS. BALANCED RIGHT/MONO and LEFT audio INPUTS.

**SPECIFICATIONS:** 300w/ch. (600w mono). Response 20-20kHz (+0 -0.25dB). Distortion 0.005%. Noise and hum -105dBa. Output impedance 2, 4 and 8 ohms. (1, 2, 4, 8 and 16 ohms in mono). Damping factor 40 or greater. Input impedance 20k unbalanced, 40k balanced. Input sensitivity 1.4v. Sentry Monitor. Power Guard.



# MC 300

STEREO POWER AMPLIFIER

McIntosh  
The Compendium



**MC 300** -Sold from 1995 - . S/N: LN1001~?????

Size 7-1/16"H, 17-1/2"W and 17-1/2"D. Weight 79 lb. **\$4,000.00**