

MC 502

STEREO POWER AMPLIFIER

McIntosh
The Compendium



FRONT PANEL: Glass with illuminated teal/gold nomenclature. **POWER GUARD** lamps: **NORMAL** or **LIMIT**. **LEFT GAIN** control. **RIGHT/MONO GAIN** control. **HEADPHONES** jack. **SPEAKERS** switch: **OFF** or **ON**. **POWER** switch: **OFF** or **ON**. **PANLOC** buttons.



BACK PANEL: **LEFT** and **RIGHT** speaker **OUTPUT** barrier strip. **UNSWITCHED AC** outlet. Power cord. **FUSE**. **MODE** switch: **STEREO** or **MONO**. **Left** and **Right (MONO)** audio **INPUT**. **INPUT LEVEL** switch: **2.5v** or **.75v**. **Panloc** mounting.

SPECIFICATIONS: **50w/ch** into 8 ohms, **75w/ch** into 2.7 to 4 ohms. (**150w** mono into 8 ohms). Response 20-20kHz (+0 -0.25dB). Distortion 0.02%. Noise and hum -95dB. Output direct coupled for 2.7 to 8 ohms. Damping factor 50 or greater. Input impedance 75k. Input sensitivity 0.75v or 2.5v. Headphone impedance: low. *Sentry Monitor. Power Guard.*



MC 502

STEREO POWER AMPLIFIER

McIntosh
The Compendium



MC 502 - Sold from December 1978 - 1989. S/N: CE1001~CE4031 (3,030 UNITS)

Size 3-5/8"H, 16"W and 14-1/2"D. Weight 27 lb. **\$1,200.00**