

# MC 7150 (& MC 7150W)

## STEREO POWER AMPLIFIER

McIntosh  
The Compendium



EARLY

**FRONT PANEL:** Glass with illuminated teal/gold nomenclature. Illuminated LEFT and RIGHT POWER OUTPUT meters (linear WATTS or DECIBELS). LEFT and RIGHT POWER GUARD lights. ⚡ LEFT GAIN control. METER switch: WATTS or HOLD. POWER switch: ON or OFF. RIGHT GAIN controls. PANLOC buttons on early **MC 7150** units.



EARLY

**BACK PANEL:** AC outlet. FUSE. Power cord. LEFT and RIGHT speaker OUTPUT barrier strips. LEFT and RIGHT audio INPUTS. Panloc mounting on early **MC 7150** units.

**SPECIFICATIONS:** 150w/ch into 8 ohms. Response 20-20kHz (+0 -0.25dB). Distortion 0.005%. Noise and hum -110dBa. Output impedance 2, 4 or 8 ohms. Damping factor 40 or greater. Input impedance 20k. Input sensitivity 1.4v. *Sentry Monitor. Power Guard.*



# MC 7150 (& MC 7150W)

## STEREO POWER AMPLIFIER

McIntosh  
The Compendium

---



In 1992, **McIntosh** increased the chassis and/or faceplate width of many of their products. Concurrently, the **Panloc** mounting system was phased out. The production cycle of the **MC 7150** spanned this change.

Early production units had the **Panloc** buttons and 16-3/16" wide faceplate. Later production units had the 17-1/2" faceplate with no **Panloc** buttons.

# MC 7150 (& MC 7150W)

## STEREO POWER AMPLIFIER

McIntosh  
The Compendium

In order to allow the customer to have a unified width for various units, a "transition" faceplate was produced and made available to **McIntosh** dealers. This faceplate was 17-1/2" wide and attached to the early, narrower chassis with special brackets. Holes were provided in the faceplate for the **Panloc** buttons.



EARLY W/ TRANSITION FACE PLATE

**MC 7150** - Sold from 1991 - 1994. S/N: GM1001~????? (**MC 7150**) and  
S/N: ??1001~????? (**MC 7150W**)

Size 5- 5/16"H, [Front panel width was 16-3/16" in early units (**MC 7150**) and 17-1/2" in later units (**MC 7150W**)]. 15-1/4"D. Weight 58 lb. **\$2,400.00**